## Summary of Selected Beneficial Use Criteria for Waterbodies Identified in the Nevada Administrative Code

			Beneficial Use Criteria																	
NAC	Name	Description	Hď	Dissolved Oxygen (mg/l)	Maximum Temperature (degrees C)	Total Phosphorus (as P - mg/l)	Total Nitrogen (as N - mg/l)	Nitrite (as N - mg/l)	Nitrate (as N - mg/l)	Total Suspended Solids (mg/L)	Turbidity (NTU)	Total Dissolved Solids (mg/l)	Chloride (mg/l)	Sulfate (mg/l)	Color (PCU)	E coli (number/milliter)				
CLASS A	WATERS																			
445A.124	Various waterbodies		6.5 - 8.5	6.0	20°	0.05 - 0.10						500								
CLASS B	WATERS			L																
	Various waterbodies		6.5 - 8.5	5.0 (nontrout waters); 6.0 (trout waters)	20° (trout waters); 24° (nontrout waters)	0.1						500								
CLASS C			L	l .		ı														
445A.126	Various waterbodies		6.5 - 8.5	5.0 (nontrout waters); 6.0 (trout waters)	20° (trout waters); 34° (nontrout waters)	0.3						500								
CLASS D																				
	Various waterbodies RIVER BASIN		6.0 - 9.0	3.0																
	West Fork Carson River	At stateline																		
445A.148	Bryant Creek	At stateline			13° (Nov-May); 17°					25			1	1	75	126 (AGM); 410				
445A.149	East Fork Carson River	At stateline																		
		Stateline to Highway 395																		
445A.151	East Fork Carson River	Highway 395 to Muller Lane	6.5 - 9.0	5.0 (Nov-May); 6.0 (Jun-Oct)																
	EF/WF & Carson River	EF at Muller to Genoa Lane & WF at stateline to Genoa Lane				0.10 (AA)		0.06	10	10	10	500 (AA	AA) 250	250						
	Carson River	Genoa Lane to Cradlebaugh Bridge							10	80	80	,								
		Cradlebaugh Bridge to Mexican Ditch Gage				18° (Nov-May); 23° (Jun-Oct)														
445A.155	Carson River	Mexican Ditch Gage to New Empire																		
445A.156	Carson River	New Empire to Dayton Bridge				ĺ	ĺ	l	11° (Nov-Mar); 24°									1		
445A.157	Carson River	Dayton Bridge to Weeks Bridge				(Apr-Jun); 28° (July-			1.0			50								
	Carson River	Weeks Bridge to Lahontan Dam			Oct)	0.06				25		<u> </u>	<u> </u>			126 (AGM); 235				
	RIVER BASIN West Walker River	At stateline	1	1	1				T .	1	1	ı				126 (AGM); 410				
445A.161	Topaz Lake	Various points in Topaz Lake												l	l	126 (AGM); 235				
445A.162		CA stateline to Wellington			l											120 (/101/1), 200				
445A.163	West Walker River	Wellington to confluence with East Walker River			13° (Nov-Apr); 17°															
445A.164	Sweetwater Creek	CA stateline to the East Walker River	1		(May-Jun); 23° (Jul-				0.06	10		10 NTU								
445A.165		At stateline	65.00	5.0 (Nov-May);	Oct)	0.10 (0.4)				90	above	E00 (AA)	250	250	75					
445A.1655		Stateline to Bridge B-1475	6.5 - 9.0	6.0 (Jun-Oct)		0.10 (AA)				80	natural	500 (AA)	250	250	/5	126 (ACM): 440				
445A.166	East Walker River	Bridge B-1475 to East/West Walker confluence								-	conditions					126 (AGM); 410				
445A.167	Walker River	East/West Walker confluence to Weber Reservoir Inlet			13° (Nov-Mar); 23° (Apr-Jun); 28° (Jul- Oct); (See Note 1)			1.0	0.06; 1.0 (See Note 2)											
	Walker River	Weber Reservoir to Walker Lake		·			State stand		not apply o											
445A.169	Desert Creek	CA stateline to the West Walker River	6-5 - 9.0		13° (Nov-Apr); 17° (May-Jun); 23° (Jul- Oct)	0.10 (AA)		0.06	10	80	10 NTU above natural	500 (AA)	250	250	75	126 (AGM); 410				
445A.1696	Walker Lake	Walker Lake	6.5 - 9.7	5.0 (See Note 3)	July	0.82		0.06	90	25	naturai					126 (AGM); 235				
CENTRAL	REGION		I.	(See Note 3)																
	Chiatovich Creek	Above highway maintenance station			12° (Nov. Apr.): 47°								1		10 PCU					
445A.172		Above center of Section 9, T2S, R34E Above hydroelectric plant	6.5 - 9.0	5.0 (Nov-May); 6.0 (Jun-Oct)	13° (Nov-Apr); 17° (May-Jun); 23° (Jul- Oct)	0.1 (AA)		0.06	10	25	10	500 (AA)	250	250	above natural	126 (AGM); 410				
<u> </u>	1				300,								ш	ш	conditions					

## Summary of Selected Beneficial Use Criteria for Waterbodies Identified in the Nevada Administrative Code

			Beneficial Use Criteria													
			S S D D												_	
NAC	Name	Description	Нd	Dissolved Oxygen (mg/l)	Maximum Temperature (degrees C)	Total Phosphoru (as P - mg/l)	Total Nitrogen (as N - mg/l)	Nitrite (as N - mg/l)	Nitrate (as N - mg/l)	Total Suspended Solids (mg/L)	Turbidity (NTU)	Total Dissolved Solids (mg/l)	Chloride (mg/l)	Sulfate (mg/l)	Color (PCU)	E coli (number/milliter)
	O RIVER BASIN	T	ı	1	1				1							1
	Virgin River	AZ stateline to Mesquite  At stateline			21° (Nov-Jun); 32°						10 NTU above					
	Virgin River Virgin River	Mesquite to river mouth at Lake Mead		5.0 (Nov-May);	(Jul-Oct)	0.1 (AA)		5	90		natural conditions	See Note			10 PCU above natural conditions	630 (AGM)
445A.178	Beaver Dam Wash	Above Schroeder Reservoir			. 13° (Nov-Apr); 17° ' (May-Jun); 23° (Jul- Oct)	0.05 (AA)		0.06			10	4				126 (AGM); 410
445A.192	Colorado River	Lake Mohave Inlet to CA stateline		6.0 (Jun-Oct)					10							
445A.193	Colorado River	Hoover Dam to Lake Mohave Inlet								25						126 (AGM); 235
445A.195	Lake Mead	Excluding area covered by NAC 445A.197	6.5 - 9.0	5.0 (See Note 5)	_			1	90		25	1000	400	500		120 (XOM), 200
445A.197	Lake Mead	West boundary of Las Vegas Bay campground to confluence of Las Vegas Wash		5.0				5	90		25	3000				
445A.199	Las Vegas Wash	Confluence of discharges from City of Las Vegas and Clark County wastewater		See Note 6				10	100	135 (See		3000				
4454 204	Las Vagas Wash	treatment plants to Telephone Road	4					10	100	Note 7)		2000				
445A.201	Las Vegas Wash Muddy River	Telephone Road to Lake Mead River source to Glendale	_			0.1 (AA)		10	100		10 NTU	3000			10 PCU	
445A.211	Muddy River	Glendale to Lake Mead			21° (Nov-Jun); 32°	0.1 (AA)			10		above	See Note			above	
445A.212	Meadow Valley Wash	Bridge above Rox to Muddy River		5.0	(Jul-Oct)	0.1 (AA)		5	90		natural conditions	4			natural conditions	630
	LT LAKE BASIN	T.,		T =	T							T ===				
445A.179	Snake Creek	Above fish hatchery	6.5 - 9.0	5.0 (Nov-May); 6.0 (Jun-Oct)	13° (Nov-Apr); 17° (May-Jun); 23° (Jul- Oct)	0.1 (AA)		0.06	10	25	10	500 (AA)	250	250	10 PCU above natural conditions	126 (AGM); 410
WESTERN	REGION		l.		<u> </u>						l		<u> </u>		00110110110	l.
	Smoke Creek	No description given	6.5 - 8.0 7.0 - 8.5 (AM)	7.5; 8.0 (Avg - Jul-Sep)	14° (Winter); 25° (Summer)	0.16 (AA); 0.23			0.1		10 JTU above natural conditions	225 (AA); 275	10		10 PCU above natural conditions	
TRUCKEE	RIVER BASIN		I.	1	l						CONTUINIONS				CONDITIONS	
	Bronco Creek	No description given	6.5 - 8.5	6.0; 7.0 (Avg: Jul-Sep)	20° (Avg: Jun-Sep); 13° (Winter); 25°	0.1 (AA);			0.9		10 JTU above	225 (AA); 300	10		10 PCU above	
445A.182	Gray Creek	No description given	7.0 - 8.5 (AM)	6.0; 7.0 (Avg: Jul-Sep)	(Summer)	0.13			0.7		natural conditions	125 (AA); 165			natural conditions	
445A.184	Truckee River	At stateline			7° (Nov-Mar); 13°											
445A.185	Truckee River	CA stateline to Idlewild			(Apr-May); 17° (Jun); 21° (Jul); 22° (Aug);	0.10 (AA)				25						
445A.186	Truckee River	Idlewild to East McCarran Blvd		1	23° (Sep-Oct)											
445A.187	Truckee River	East McCarran Blvd to Lockwood	6.5 - 9.0	5.0 (Apr-Oct);	13° (Nov-Mar); 21° (Apr); 22° (May); 23°			0.04	2		10	500 (AA)	250	250	75	126 (AGM); 410
445A.188	Truckee River	Lockwood to Derby Dam		6.0 (Nov-Mar)	(Jun-Oct); (See Notes 8 & 9)	.05 (AA)	1.2; 0.75			50		( 9			-	
445A.189	Truckee River	Derby Dam to Wadsworth	-		13° (Nov-Mar); 14° (Apr-Jun); 25° (Jul-Oct); (See Note 9)	.00 (AA)	(AA)			30						
445A.190	Truckee River	Wadsworth to Pyramid Lake					State stand	dards do	not apply o	n tribal lan	ds	<u> </u>				
445A.191	Lake Tahoe	Lake Tahoe	7.0 - 8.4	See Note 10	10° (Oct-May); 20°		0.32; 0.25				See Note 12		5; 3	2		
4454 40:-					(Jun-Sep)	11	(AA)	0.05	40	0.5	- 10	(AA)	(AA)	0.50		126
445A.1915	Tributaries to Lake Tahoe	All tributaries	6.5 - 9.0	6.0	,,	0.05		0.06	10	25	10	500 (AA)	250	250	75	

## Summary of Selected Beneficial Use Criteria for Waterbodies Identified in the Nevada Administrative Code

			Beneficial Use Criteria													
NAC	Name	Description	Hd	Dissolved Oxygen (mg/l)	Maximum Temperature (degrees C)	Total Phosphorus (as P - mg/l)	Total Nitrogen (as N - mg/l)	Nitrite (as N - mg/l)	Nitrate (as N - mg/l)	Total Suspended Solids (mg/L)	Turbidity (NTU)	Total Dissolved Solids (mg/l)	Chloride (mg/I)	Sulfate (mg/l)	Color (PCU)	E coli (number/milliter)
	T RIVER BASIN		,	,					•			1				
		Source to Osino	6.5 - 9.0	5.0				1.0	10	80 (AM)	50	500 (AA)	250			126 (AGM); 410
		Osino to Palisade				0.1 (??)										
		Palisade to Battle Mountain												250		
		Battle Mountain to State Highway 789												200	effects	
		Comus to Imlay														
		Imlay to Woosley										1000				126 (AGM); 235
SNAKE RIV																
		Entire reach			21° (May-Oct); 13° (Nov-Apr)							500	250			126 (AGM); 410
		Entire reach														
		Entire reach				0.1		0.06							10 PCU	
		Entire reach													above natural	
		Upstream from Jarbidge	6.5 - 9.0	6					10	25	10					
		Jarbidge to stateline			21° (May-Oct); 7°										conditions	
445A.221		Entire reach			(Nov-Apr)										CONTUINIONS	
		Wildhorse Reservoir to Mill Creek														
		Mill Creek to New China Dam														
		New China Dam to stateline					State stand		not apply o							
445A.225	South Fork Owyhee River	Entire reach	6.5 - 9.0	6	21° (May-Oct); 13°	0.1		0.06	10	25	10	500	250		10 PCU	126 (AGM); 410
					(Nov-Apr)										above	
															natural	
															conditions	

All criteria are for single values unless otherwise noted as follows:

AA = annual average

AGM = annual geometric mean

AM = annual median

- 1. The temperature beneficial use standard is 21 degrees C from February through June when Lahontan cutthroat trout are present in this reach.
- 2. The nitrite beneficial use standard is 0.06 mg/l from February through June when Lahontan cutthroat trout are present in this reach.
- 3. When lake is stratified, the dissolved oxygen criteria applies only to the epilimnion.
- 4. The flow weighted annual average concentrations for total dissolved solids in mg/l at the three lower main stem stations of the Colorado River are as follows: Below Hoover Dam = 723, Below Parker Dam = 747; Imperial Dam = 879
- 5. Standard applies to the epilimnion or average in water column during periods of stratification.
- 6. Aerobic conditions are established as a goal rather than a standard. Aerobic conditions is intended to mean the absence of objectionable odors that may by caused by wastewater discharges in excess of existing odors.
- 7. Total suspended solids standard does not apply when flows are greater than 110 percent of average flow as measured at nearest gage. Average flow is defined as 12-month rolling average of the average monthly flow.
- 8. When flows are adequate to induce spawning runs of cui-ui and Lahontan cutthroat trout, the standard is 14 degrees C from April through June.
- 9. The desired temperature for the protection of juvenile Lahontan cutthroat trout is 21 degrees C, even though that temperature is not attainable at all times.
- 10. DO standard presented as minimum allowable percent of saturation of 90 percent.
- 11. Standard presented as maximum soluble phosphorus annual average concentration of 7.0 mg/l
- 12. Turbidity must not exceed 3 NTU at any point in the lake too shallow to determine a reliable vertical extinction coefficient.